

Pushbutton, RMQ-Titan, Flat, maintained, red, Blank, Bezel: titanium

Part no. **M22-DR-R**
216617

Product name			Eaton Moeller® series M22 Pushbutton
Part no.			M22-DR-R
EAN			4015082166175
Product Length/Depth			30 millimetre
Product height			30 millimetre
Product width			30 millimetre
Product weight			0.011 kilogram
Compliances			CE Marked
Certifications			CSA Std. C22.2 No. 94-91 UL 508 CSA Std. C22.2 No. 14-05 IEC 60947-5 EN 60947-5 VDE IEC/EN 60947 UL IEC/EN 60947-5 CSA Class No.: 3211-03 CE CSA UL Category Control No.: NKCR CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 CSA File No.: 012528 UL File No.: E29184 VDE 0660 LR GL DNV
Product Tradename			M22
Product Type			Pushbutton
Product Sub Type			None
Bezel color			Titanium
Bezel material			Plastic
Design			Flat Classical
Fitted with:			Front ring
Functions			Stay-put/spring-return function can be changed on device
Inscription			Blank
Degree of protection			IP66 NEMA 4X NEMA 12 NEMA 13 IP67 IP69K NEMA 3R
Degree of protection (front side)			NEMA 4X IP67/IP69K
Lifespan, mechanical			1,000,000 Operations (AC operated)
Opening diameter			22.5 mm
Operating frequency			1800 Operations/h
Product category			RMQ-Titan
Size			Front dimensions: 22 x 22 mm
Type			Pushbutton actuator
Mounting position			As required
Shock resistance			Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Ambient storage temperature - min			40 °C
Ambient storage temperature - max			80 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Connection to SmartWire-DT			With SWD-RMQ connections Yes
Actuating force			5 N
Actuator color			Red
Actuator function			Switching function latching Maintained
Force for positive opening - min			0 N
Equipment heat dissipation, current-dependent P _{vid}			0 W
Heat dissipation capacity P _{diss}			0 W
Heat dissipation per pole, current-dependent P _{vid}			0 W
Rated operational current for specified heat dissipation (I _n)			0 A
Static heat dissipation, non-current-dependent P _{vs}			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ec1@ss10.0.1-27-37-12-10 [AKF028014])			
Colour button			Red
Number of command positions			1
Construction type lens			Round
Hole diameter		mm	22.5
Width opening		mm	0
Height opening		mm	0

Type of button			Flat
Suitable for illumination			No
With protective cover			No
Labelled			No
Switching function latching			Yes
Spring-return			No
With front ring			Yes
Material front ring			Plastic
Colour front ring			Titanium
Degree of protection (IP), front side			IP67/IP69K
Degree of protection (NEMA), front side			4X