DATASHEET - DILEEM-10-EA(230V50HZ,240V60HZ)

Contactor, 230 V 50 Hz, 240 V 60 Hz, 3 pole, 380 V 400 V, 3 kW, Contacts N/O = Normally open= 1 N/O, Screw terminals, AC operation

Powering Business Worldwide

Part no. DILEEM-10-EA(230V50HZ,240V60HZ)
189979

Product name			Eaton Moeller® series DILEEM Mini contactor
Part no.			DILEEM-10-EA(230V50HZ,240V60HZ)
EAN			4015081879755
Product Length/Depth			52 millimetre
Product height			58 millimetre
Product width			45 millimetre
Product weight			0.17 kilogram
Compliances			RoHS conform CE CE Marked
Product Tradename			DILEEM
Product Type			Mini contactor
Product Sub Type			None
Voltage type			AC
Rated operational power at AC-3, 380/400 V, 50 Hz			3 kW
Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V			22 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V			6.6 A
Rated control supply voltage (Us) at AC, 50 Hz - min			230 V
Rated control supply voltage (Us) at AC, 50 Hz - max			230 V
Rated control supply voltage (Us) at AC, 60 Hz - min			240 V
Rated control supply voltage (Us) at AC, 60 Hz - max			240 V
Rated control supply voltage (Us) at DC - min			0 V
Rated control supply voltage (Us) at DC - max			0 V
Number of auxiliary contacts (normally closed contacts)			0
Number of auxiliary contacts (normally open contacts)			1

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage Us at AC 50HZ		V	230 - 230
Rated control supply voltage Us at AC 60HZ		V	240 - 240
Rated control supply voltage Us at DC		V	0 - 0
Voltage type for actuating			AC
Rated operation current Ie at AC-1, 400 V		A	22
Rated operation current Ie at AC-3, 400 V		A	6.6
Rated operation power at AC-3, 400 V		kW	3
Rated operation current Ie at AC-4, 400 V		A	5
Rated operation power at AC-4, 400 V		kW	2.2
Rated operation power NEMA		kW	2.2
Modular version			No
Number of auxiliary contacts as normally open contact			1
Number of auxiliary contacts as normally closed contact			0
Type of electrical connection of main circuit			Screw connection
Number of normally closed contacts as main contact			0

Number of normally open contacts as main contact				3

© 04/2023 by Eaton Industries GmbH